



Technical drawing of a cable tray system, showing a side view and a top view.

Side View Dimensions:

- Tray Width: 600
- Cable Spacing: 50
- Cable Diameter: 53
- Tray Height: 60
- Tray Length (Top Section): 640
- Tray Length (Bottom Section): 1400
- Tray Height (Bottom Section): 60
- Tray Length (Total): A
- Switch Box Dimensions: 40 (height), 150 (width)
- Plug Dimensions: 150 (width), 40 (height)
- Plug Label: E L B 付差込みプラグ
- Plug Label: アース
- Plug Label: コード長 1m
- Plug Label: スイッチBOX

Top View Dimensions:

- Tray Width: 90
- Cable Spacing: 53
- Tray Height: 55

重量 : 24.0 kg
 定格電圧 : AC 100V
 定格消費電力 : 600W
 漏電保護器 : 100V, AC, 15A, 15mA
 (差し込みプラグELB)
 50/60HZ兼用
 アース線 : Y端子接続 長さ150mm
 温度ヒューズ : 91℃
 温度調整範囲 : 30℃~70℃
 凍結温度 : -13℃
 電源コード長 : 1000mm

The technical drawing shows a rectangular plate with overall dimensions of 90 units by 40 units. The horizontal distance from the left edge to the center of the first hole is 10 units. The distance between the centers of the two holes is 45 units. The distance from the center of the second hole to the right edge is 25 units. A dashed circle indicates a hole with a diameter of 25 units. A dimension line labeled 10R points to the corner radius of the plate.

ビスA	ビスB
コーチねじ 8×60 	コーススレッド 5.3×40
プラグ 10×50 	

図番					図名	YAE09/R-600L 100V 600W 横壁支持					
製図	小松	担当	馬淵	検図	大久	尺度	/	投影法	三角法	日付	20/06/15
 ピーエス工業株式会社						備考					